

## B-MOUNT电池



BM-HV300


### BM-HV300

|             |                                      |
|-------------|--------------------------------------|
| 容量:         | 28.8V 10.2Ah 293Wh                   |
| 输出:         | 250W/10A (Max)                       |
| D-TAP*2输出:  | 16V/4.0A (64W Max), 16V恒压输出          |
| USB-A输出:    | 5V/2A                                |
| USB-C输入/输出: | 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A |
| 尺寸:         | 154 (L) mm × 100 (W) mm × 87 (T) mm  |
| 重量:         | 1680g                                |




### B-mount双路同步充电器-FX-BM2LC

|       |                                    |
|-------|------------------------------------|
| 输入:   | 100~240VAC 47~63Hz                 |
| 充电输出: | 33.6V / 3.75A × 2                  |
| 功率:   | 280W                               |
| 适用于:  | FXLION B-mount锂离子电池充电              |
| 尺寸:   | 230(L)mm × 172.92(W)mm × 75.5(H)mm |
| 重量:   | 1080g                              |



### FX-BM24D-V型电池转B-mount输出适配器

|            |                                          |
|------------|------------------------------------------|
| 输入:        | 10-29.4V, 可使用14.8V电池和26V电池               |
| B-Mount输出: | 30V/6A (Max), 180W的输出可适配arri super35等摄像机 |
| 2*D-Tap输出: | 12V/4A (Max), 12V 恒压输出, 可适配所有的监视器和摄像机外设  |
| 尺寸:        | 146.5mm × 102.5mm × 42.8mm               |
| 重量:        | 380g                                     |



BM-HV200


### BM-HV200

|             |                                       |
|-------------|---------------------------------------|
| 容量:         | 28.8V 6.8Ah 196Wh                     |
| D-TAP*2输出:  | 16V/4.0A (64W Max)                    |
| 电池输出:       | 21.6V~33.6V/250W (Max)                |
| USB-A输出:    | 5V/2A                                 |
| USB-C输入/输出: | 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A  |
| 尺寸:         | 154 (L) mm × 100 (W) mm × 68.5 (T) mm |
| 重量:         | 1150g                                 |



### B-mount四路同步充电器-FX-BM4LC

|     |                            |
|-----|----------------------------|
| 输入: | 100~240VAC 47~63Hz         |
| 输出: | 33.6V / 3.75A × 4          |
| 功率: | 550W                       |
| 特点: | 四路同步充, 每一路都是4A充电           |
| 尺寸: | 245(L) × 154(W) × 170(H)mm |
| 重量: | 3000g                      |



### B-mount双路挂板-FX-BM-AR60

|                                |                           |
|--------------------------------|---------------------------|
| ARRI Skypanel S60/S30/S120专用挂板 |                           |
| 输入:                            | 28.8VX2 (电池)              |
| DC输出:                          | 24.0~33.6V                |
| 尺寸:                            | 319(L) × 109(W) × 65(H)mm |
| 重量:                            | 620g                      |

